

Edge: Canny

Dr. Tushar Sandhan

Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1

Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1

+45 degrees

2	-1	-1
-1	2	-1
-1	-1	2

Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1

+45 degrees

2	-1	-1
-1	2	-1
-1	-1	2

Vertical

-1	2	-1
-1	2	-1
-1	2	-1

Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1

+45 degrees

2	-1	-1
-1	2	-1
-1	-1	2

Vertical

-1	2	-1
-1	2	-1
-1	2	-1

-45 degrees

-1	-1	2
-1	2	-1
2	-1	-1

Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1

+45 degrees

2	-1	-1
-1	2	-1
-1	-1	2

Vertical

-1	2	-1
-1	2	-1
-1	2	-1

-45 degrees

-1	-1	2
-1	2	-1
2	-1	-1



Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1



+45 degrees

2	-1	-1
-1	2	-1
-1	-1	2



Vertical

-1	2	-1
-1	2	-1
-1	2	-1

-45 degrees

-1	-1	2
-1	2	-1
2	-1	-1

Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1




+45 degrees

2	-1	-1
-1	2	-1
-1	-1	2



Vertical

-1	2	-1
-1	2	-1
-1	2	-1



-45 degrees

-1	-1	2
-1	2	-1
2	-1	-1

Introduction

- Directions with operators

Horizontal

-1	-1	-1
2	2	2
-1	-1	-1




+45 degrees

2	-1	-1
-1	2	-1
-1	-1	2



Vertical

-1	2	-1
-1	2	-1
-1	2	-1



-45 degrees

-1	-1	2
-1	2	-1
2	-1	-1



Kirsch operator (compass)

- Directions with Kirsch
 - direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$

Kirsch operator (compass)

- Directions with Kirsch

- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$

$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$

Kirsch operator (compass)

- Directions with Kirsch

- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$

$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$



Kirsch operator (compass)

- Directions with Kirsch


- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$

$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$



$\mathbf{g}^{(1)}$



Kirsch operator (compass)

- Directions with Kirsch

- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$


$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$



$\mathbf{g}^{(1)}$



$\mathbf{g}^{(2)}$



Kirsch operator (compass)

- Directions with Kirsch


- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$

$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$




$\mathbf{g}^{(1)}$



$\mathbf{g}^{(2)}$



$\mathbf{g}^{(3)}$



Kirsch operator (compass)

- Directions with Kirsch


- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$


$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix}, \quad \mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$




$\mathbf{g}^{(1)}$




$\mathbf{g}^{(2)}$



$\mathbf{g}^{(3)}$



$\mathbf{g}^{(4)}$



Kirsch operator (compass)

- Directions with Kirsch

- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$

$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix},$$


$$\mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix},$$

$$\mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix},$$

$$\mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$




$\mathbf{g}^{(1)}$




$\mathbf{g}^{(2)}$



$\mathbf{g}^{(3)}$



$\mathbf{g}^{(4)}$



$h_{n,m}$



Kirsch operator (compass)

- Directions with Kirsch

- direction is defined by the mask that produces max edge magnitude

$$h_{n,m} = \max_{z=1,\dots,8} \sum_{i=-1}^1 \sum_{j=-1}^1 g_{ij}^{(z)} \cdot f_{n+i,m+j}$$

$$\mathbf{g}^{(1)} = \begin{bmatrix} +5 & +5 & +5 \\ -3 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix},$$

$$\mathbf{g}^{(2)} = \begin{bmatrix} +5 & +5 & -3 \\ +5 & 0 & -3 \\ -3 & -3 & -3 \end{bmatrix},$$

$$\mathbf{g}^{(3)} = \begin{bmatrix} +5 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & -3 & -3 \end{bmatrix},$$

$$\mathbf{g}^{(4)} = \begin{bmatrix} -3 & -3 & -3 \\ +5 & 0 & -3 \\ +5 & +5 & -3 \end{bmatrix}$$




$\mathbf{g}^{(1)}$




$\mathbf{g}^{(2)}$



$\mathbf{g}^{(3)}$




$\mathbf{g}^{(4)}$




$h_{n,m}$




Kirsch operator (compass)



Kirsch operator (compass)




Kirsch operator (compass)



North




Kirsch operator (compass)



North



Kirsch operator (compass)




North



North West



Kirsch operator (compass)




North



North West



Kirsch operator (compass)



North




North West



West



Kirsch operator (compass)



North




North West



West



Kirsch operator (compass)



North



North West




West



South West



Kirsch operator (compass)



North



North West




West



South West



Kirsch operator (compass)



North



North West



West




South West



South



Kirsch operator (compass)



North



North West



West



South West




South



South East



Kirsch operator (compass)



North



North West



West



South West



South




South East



East



Kirsch operator (compass)



North



North West



West



South West



South



South East



East



North East



Introduction

- Single point thick edges

input



Introduction

- Single point thick edges

input



Introduction

- Single point thick edges

input



Canny edges




Introduction

- Single point thick edges

input



Canny edges



Introduction

- Single point thick edges


input



Canny edges



Canny PCB edges



Edge


- What would be important steps in edge det.

Edge

- What would be important steps in edge det.
 - Smooth derivatives


Edge

- What would be important steps in edge det.
 - Smooth derivatives





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning





Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning
 - Linking






Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning
 - Linking



Edge

- What would be important steps in edge det.
 - Smooth derivatives
 - Thresholding
 - Thinning
 - Linking



Canny edge detector

- Objectives

Canny edge detector

- Objectives
 - low error rate
 - all edges should be found

Canny edge detector

- Objectives

- low error rate
 - all edges should be found
- good localization of edges
 - centre of true edge at i^{th} pixel : c_i
 - obtained edge point at i^{th} pixel: e_i
 - minimize the distance $\|c_i - e_i\|_2$

Canny edge detector

- Objectives

- low error rate
 - all edges should be found
- good localization of edges
 - centre of true edge at i^{th} pixel : c_i
 - obtained edge point at i^{th} pixel: e_i
 - minimize the distance $\|c_i - e_i\|_2$
- single point edge response
 - 1 point for each true edge point

Canny edge detector

- Image derivatives
 - input image $f(x, y)$
 - smoothed $f_s(x, y)$
 - any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

Canny edge detector

- Image derivatives
 - input image $f(x, y)$
 - smoothed $f_s(x, y)$
 - any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

Canny edge detector

- Image derivatives

- input image $f(x, y)$
- smoothed $f_s(x, y)$
- any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

$$g_x(x, y) = \partial f_s(x, y) / \partial x \qquad g_y(x, y) = \partial f_s(x, y) / \partial y$$

Canny edge detector

- Image derivatives

- input image $f(x, y)$
- smoothed $f_s(x, y)$
- any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

$$g_x(x, y) = \partial f_s(x, y) / \partial x$$

$$g_y(x, y) = \partial f_s(x, y) / \partial y$$

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

Canny edge detector

- Image derivatives

- input image $f(x, y)$
- smoothed $f_s(x, y)$
- any operator can be used to get $g_x(x, y)$, $g_y(x, y)$

$$G(x, y) = e^{-\frac{x^2 + y^2}{2\sigma^2}}$$

$$f_s(x, y) = G(x, y) \star f(x, y)$$

$$g_x(x, y) = \partial f_s(x, y) / \partial x$$

$$g_y(x, y) = \partial f_s(x, y) / \partial y$$

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning
 - $M_s(x, y)$ wide ridges around local maxima
 - ridges thinning is needed
 - non-max suppression
 - suppress where?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning
 - $M_s(x, y)$ wide ridges around local maxima
 - ridges thinning is needed
 - non-max suppression
 - suppress where?
 - on the ridges

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning

- $M_s(x, y)$ wide ridges around local maxima
- ridges thinning is needed
- non-max suppression
 - suppress where?
 - on the ridges
 - how?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$

Canny edge detector

- Thinning

- $M_s(x, y)$ wide ridges around local maxima
- ridges thinning is needed
- non-max suppression
 - suppress where?
 - on the ridges
 - how?
 - walking along edge normals?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$


Canny edge detector

■ Thinning

- $M_s(x, y)$ wide ridges around local maxima
- ridges thinning is needed
- non-max suppression
 - suppress where?
 - on the ridges
 - how?
 - walking along edge normals?

$$M_s(x, y) = \|\nabla f_s(x, y)\| = \sqrt{g_x^2(x, y) + g_y^2(x, y)}$$

$$\alpha(x, y) = \tan^{-1} \left[\frac{g_y(x, y)}{g_x(x, y)} \right]$$




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction



Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction





Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction






Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p





Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p




$$\frac{y - y_0}{x - x_0} = \frac{y_1 - y_0}{x_1 - x_0}$$




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p




$$\frac{y - y_0}{x - x_0} = \frac{y_1 - y_0}{x_1 - x_0}$$

$$y = y_0 + (x - x_0) \frac{y_1 - y_0}{x_1 - x_0}$$



Canny edge detector


- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p



$$\frac{y - y_0}{x - x_0} = \frac{y_1 - y_0}{x_1 - x_0}$$


$$y = y_0 + (x - x_0) \frac{y_1 - y_0}{x_1 - x_0}$$

$$= y_0 \left(1 - \frac{x - x_0}{x_1 - x_0} \right) + y_1 \left(\frac{x - x_0}{x_1 - x_0} \right)$$




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p




Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p






Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p






Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p





Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p



Canny edge detector

- Thinning
 - non-max suppression:
checks whether pixel is local maxima
in grad direction
 - linear interpolation for missing
locations e.g. r, p



after non-max supp



Canny edge detector



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!
 - two instruments of thresholds: Hysteresis



Canny edge detector

- LINKING Points
 - Canny edge detector
 - It starts with one thing: gradients
 - In the end, it doesn't even matter: which operators have been used
 - at last we have to link the non-suppressed ones!
- two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}



Canny edge detector

- Hysteresis

Canny edge detector

- Hysteresis
 - two instruments of thresholds: Hysteresis

Canny edge detector

- Hysteresis
 - two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}

Canny edge detector

- Hysteresis
 - two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}



Canny edge detector

- Hysteresis
 - two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}

after non-max supp



Canny edge detector


- Hysteresis
 - two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}



after non-max supp



double thresh



Canny edge detector


- Hysteresis
 - two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}




after non-max supp



double thresh



hysteresis



Canny edge detector


- Hysteresis
 - two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}




after non-max supp



double thresh



hysteresis



White – strong edges
Blue – weak connect
Red – remaining weak
edges (non-edge)

Canny edge detector


- Hysteresis
 - two instruments of thresholds: Hysteresis
 - a. find all edge points using TH^{high}
 - b. from each strong point follow the both side direction \perp to the edge normal
 - c. in that directions, construct the contours of connected edge points
 - d. mark all points greater than TH_{low}




after non-max supp



double thresh



hysteresis



White – strong edges
Blue – weak connect
Red – remaining weak edges (non-edge)

Canny edge detector

- Entire algorithm composition:

Canny edge detector

- Entire algorithm composition:
 1. Filter image with derivatives of Gaussian
 2. Get M, α
 3. Non-max suppression
 - thin multi-pixel wide edges to a single pixel widths
 4. Linking: the hysteresis
 - 2 thresholds: TH_{low} , TH^{high}
 - TH^{high} : to start an edge
 - TH_{low} : continue started edge

Canny edge detector

Canny edge detector

- Speeding up the beats of operations
 - binning the α (angles)
 - 4 directions

Canny edge detector

- Speeding up the beats of operations
 - binning the α (angles)
 - 4 directions

Horizontal

+45 degrees

Vertical

-45 degrees

Canny edge detector

- Speeding up the beats of operations


- binning the α (angles)
- 4 directions

Horizontal

+45 degrees

Vertical

-45 degrees



Canny edge detector

- Speeding up the beats of operations



- binning the α (angles)
- 4 directions

Horizontal

+45 degrees


Vertical

-45 degrees



Canny edge detector

- Speeding up the beats of operations
 - binning the α (angles)
 - get the directional bin $Bin()$ closest to α
 - from previous operations edge: $M(x, y)$
 - suppression
 - If $M(x', y') > M(x, y)$ then $M(x, y) \rightarrow 0$
 - where neighbors $x', y' \leftarrow Bin(x, y)$



Canny edge detector

1. **Smoothing:** Blurring of the image to remove noise.
2. **Finding gradients:** The edges should be marked where the gradients of the image has large magnitudes.
3. **Non-maximum suppression:** Only local maxima should be marked as edges.
4. **Double thresholding:** Potential edges are determined by thresholding.
5. **Edge tracking by hysteresis:** Final edges are determined by suppressing all edges that are not connected to a very certain (strong) edge.


Canny edge detector

1. **Smoothing:** Blurring of the image to remove noise.
2. **Finding gradients:** The edges should be marked where the gradients of the image has large magnitudes.
3. **Non-maximum suppression:** Only local maxima should be marked as edges.
4. **Double thresholding:** Potential edges are determined by thresholding.
5. **Edge tracking by hysteresis:** Final edges are determined by suppressing all edges that are not connected to a very certain (strong) edge.



Canny edge detector

1. **Smoothing:** Blurring of the image to remove noise.
2. **Finding gradients:** The edges should be marked where the gradients of the image has large magnitudes.
3. **Non-maximum suppression:** Only local maxima should be marked as edges.
4. **Double thresholding:** Potential edges are determined by thresholding.
5. **Edge tracking by hysteresis:** Final edges are determined by suppressing all edges that are not connected to a very certain (strong) edge.



Canny edge detector

- Varying σ

input



Canny edge detector

- Varying σ

input



Canny edge detector

- Varying σ

input



Canny edge detector

- Varying σ

input



σ small



Canny edge detector

- Varying σ

input



σ small



σ large



Canny edge detector

- Comparing other edge detectors

input



Canny edge detector

- Comparing other edge detectors

input



Sobel with TH




Canny edge detector

- Comparing other edge detectors

input



Sobel with TH



LoG zero crossings




Canny edge detector

- Comparing other edge detectors

input



Sobel with TH



LoG zero crossings



Canny



Canny edge detector

- Comparing other edge detectors

input




Canny edge detector

- Comparing other edge detectors

input



Sobel with TH




Canny edge detector

- Comparing other edge detectors


input



Sobel with TH



LoG zero crossings




Canny edge detector

- Comparing other edge detectors


input




Sobel with TH



LoG zero crossings



Canny



A canny player with a Canny edge!



A canny player with a Canny edge!




Messi

A canny player with a Canny edge!




Messi



A canny player with a Canny edge!



Messi




Sobel

A canny player with a Canny edge!



Messi




Sobel



A canny player with a Canny edge!



Messi



Sobel



Laplacian


A canny player with a Canny edge!



Messi



Sobel




Laplacian



A canny player with a Canny edge!



Messi



Sobel



Laplacian




Canny

A canny player with a Canny edge!



Messi

who will you
go with?



Sobel



Laplacian



Canny

Conclusion

- Canny edge detector

Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Conclusion

- Canny edge detector

□ Single point thick edges

□ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses



Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Go with a 'canny' player, for accuracy



Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Go with a 'canny' player, for accuracy

And with uSΘin BΘLt, for speed!



Conclusion

- Canny edge detector

❑ Single point thick edges

❑ Canny operations

- Thinning: non-max suppression
- Linking: double TH hysteresis
- High accuracy is paid via computational expenses

Go with a 'canny' player, for accuracy

And with uSΘin BΘLt, for speed!

